

MSFL15W | 15W Solar Flood Light



Built-in solar controller - set to run 100% for 6 hours then 70% for remainder of night Battery Capacity and type: 14.4V Lithium Battery Charge Time with full sunshine: 3 Hours Light: SMD – Cool White 5K Light Coverage: Approximately 8m x 8m Hardware: Includes all steel bracketing, battery, light, solar panels, controller and all nuts and bolts required for installation. Pole not included.

Luminaire Power	15,00 W
Lumen	1 700
LED Type	SMD
LED Name	Philips Lumileds
Lens	PMMA
LED Temperature	5000K
Beam Angle	60deg
Coverage	40m ²
CRI	>80
Battery Chemistry	Lithium-Ion
Battery AH	16.8Ah
Battery Wh	240
Battery Cycles	>2000
Panel Total W	50
Panel Voltage	18V
Panel Current	2.78A
Controller Type	PWM SmartLED
Controller Size	10A
Controller Program	6hrs 100%, 7hrs 70%
Controller Protections	Over-Charge, Over-Discharge, Temp Compensation
Controller Sensor	Built-in Day/Night Sensor
Operating Temp	-10 to 45 deg C
IP Rating	IP68
Mounting Height	2-4m
Pole-to-Pole	N/A
Pole Top Size	90
Power Box Type	MB-67-S
Steel Description	High Quality Galvanized
Warranty	3 Years
Pole or Base	Not Included

