

MSSL20WD | 20W Solar Street Light Double



Our street light systems are ideal for lighting streets, roads, carpark areas and perimeters. Built-in solar controller - set to run 100% for 6 hours then 70% for remainder of night Battery Capacity and type: 14.4 V Lithium Battery Charge Time with full sunshine: 3 Hours Light: SMD – Cool White 5K Light Coverage: Approximately 15m x 8m Pole spacing: 20M. Pole Height 4 - 6m Hardware: Includes all steel bracketing, battery, light, solar panels, controller and all nuts and bolts required for installation. Pole not included.

| | |
|------------------------|--------------|
| Luminaire Power | 20,00 W |
| Lumen | 4 800 |
| LED Type | |
| LED Name | |
| Lens | |
| LED Temperature | |
| Beam Angle | |
| Coverage | |
| CRI | |
| Battery Chemistry | |
| Battery AH | |
| Battery Wh | 675 |
| Battery Cycles | |
| Panel Total W | 160 |
| Panel Voltage | |
| Panel Current | |
| Controller Type | |
| Controller Size | |
| Controller Program | |
| Controller Protections | |
| Controller Sensor | |
| Operating Temp | |
| IP Rating | |
| Mounting Height | |
| Pole-to-Pole | |
| Pole Top Size | 101 |
| Power Box Type | MB-67-D |
| Steel Description | |
| Warranty | |
| Pole or Base | Not Included |

