

## MSFL30W6 | 30W Solar Flood Light - 6Hr



Our flood light systems are ideal for lighting general areas which require wide angle lighting. This version is set to only run for 6 hours from dusk. Built-in solar controller - set to run 100% for 6 hours Battery Capacity and type: 14.4V Lithium Battery Charge Time with full sunshine: 3 Hours Light: SMD – Cool White 5K Light Coverage: Approximately 20m x 20m Hardware: Includes all steel bracketing, battery, light, solar panels, controller and all nuts and bolts required for installation. Pole not included.

Luminaire Power	30,00 W
Lumen	3 600
LED Type	SMD
LED Name	Philips Lumileds
Lens	PMMA
LED Temperature	5000K
Beam Angle	60deg
Coverage	130m <sup>2</sup>
CRI	>80
Battery Chemistry	Lithium-Ion
Battery AH	20Ah
Battery Wh	290
Battery Cycles	>2000
Panel Total W	50
Panel Voltage	18V
Panel Current	2.78A
Controller Type	PWM SmartLED
Controller Size	10A
Controller Program	6hrs 100%
Controller Protections	Over-Charge, Over-Discharge, Temp Compensation
Controller Sensor	Built-in Day/Night Sensor
Operating Temp	-10 to 45 deg C
IP Rating	IP68
Mounting Height	2-6m
Pole-to-Pole	N/A
Pole Top Size	90
Power Box Type	MB-67-S
Steel Description	High Quality Galvanized
Warranty	3 Years
Pole or Base	Not Included

